



Standalone EM access controller

(with ability of learning maximum **1,000** cards)

PP-360



Features

- Read 125 KHz proximity card with EM chip internally for standard model.
- The system parameters are stored in non-volatile memory for 10 years data retention as power off without any external power supply.
- 1000 card holders with 8 digits I.D. number by learning reads.
- The door released time, door monitoring time could be freely programmed for 1, 5, 10 seconds or normal open/normal close.
- With exit push button for exit or remote exit control.
- Low power CMOS CPU with watch-dog function to assure best performance.
- ABS case for easy installation.

Specification

Dimensions	: 118(L) x 75(W) x 17(H)mm
Net weight	: 98g \pm 5%
Power supply	: DC 12V \pm 10%, 40mA(Standby) / 70mA(Work)
Operating temperature	: 0°C ~ 70°C
Operating humidity	: 10%~90%
Card standard	: EM 125KHz
Waterproof	: Yes

PONGEE INDUSTRIES CO., LTD.

5F., No.738, Chung-Cheng Rd., Chung-Ho District, New Taipei City 23511, Taiwan

Tel : 886-2-82280198

Fax : 886-2-82280191

E-mail : pongee@pongee.com.tw

Website:<http://www.pongee.com>

We reserve the right to change the specification without notice or obligation!